

Telephone No. 021-99231418 Fax #: 021-99231084 Email: sindhprisons@gmail.com

## OFFICE OF THE INSPECTOR GENERAL OF PRISONS, SINDH

Pir Illahi Buksh Road Muslimabad, Karachi.

10.SB-11 9407 Dated: 25 MAY 2015

## CORRIGENDUM

Technical Specification of Digital X-Ray Machines 300mA whose bids have been invited on 03.06.2015. N.I.T published in various newspapers i.e. Daily Jang, Daily The Nation, Daily Ibrat, Daily Kaleem etc vide No.INF-KRY-1934/2015 and bid document hoisted on SPPRA website vide serial No.24223 is modified here as under:

X-RAY MACHINE

300mA-125KVP Full Wave Solid State Silicon Rectified X-Ray Generator for

Radiography.

RATING

RADIOGRAPHY: 40 to 125 KVP

Small Focus: 50mA at 40 to 125 KVP

100mA at 40 to 125 KVP

Large Focus: 300mA at 40 to 125 KVP

200mA at 40 to 100 KVP

TIMER

Solid State Electronic Timer with timing range from 0.01 to 5 Sec. (in 24

steps).

CONTROL

Consisting of Push to On & OFF Switches, with Voltmeter, mA meter, Quick trip-overload circuit breaker (Automatic safety system to block unwanted exposure factors beyond Tube Rating), Voltage Compensator, Major & Minor KV selector, Tube overload indicator provided. Digital Display of active KVP & mAs. Electronic overload for protection of tube H.V. Cables & H.T. Tank. Independent Fluoro KVP Selector. In built Ready & X-Ray Switch on Control.

HV TRANSFORMER

Compact Heavy Duty Transformer comprising HV Silicon Rectifiers, HT Transformer, Filament Transformer, Federal Bushings all immersed in oil.

ACCESSORIES

Hand Switch with Flexible long cord enables the operator to keep away from the Radiation area during exposure.

- Aluminum Filter.

- Light Beam Diaphragm.

POWER SUPPLY REQUIREMENT

400-440V AC, 50 Hz, Three Phase - Max. Allowable line Regulation ± 10%.

TUBE UNIT

One Rotating Anode Tube Unit with dual Focal tube inserts having small focal Spot 1.0 mm sq. and Large 2.0mm. Sq.

ANODE HEAT STORAGE CAPACITY: 140KHU

HV CABLE

1 Pair of 10 meter High Voltage Cables:

Sleevings - Straight.

STN

Floor to Ceiling Stand & with Counter Balanced Tube Head (Rotatable ± 180 Degree), 360 Degree Rotatable; mounted on Floor Ceiling Rails for

convenient movements.

## MEDFLOAT

Horizontal Bucky Table with Floating table top (manually operated) for Over couch & Bucky Radiography of various body parts. The Table consists of Motorized reciprocating bucky with Grid of size 17 ¼" x 18 7/8" having Grid Ratio of 8:1, 85 lines/Inch & a stainless steel cassette Tray. The Bucky travels the entire length of the table and can be locked at any desired position by a lock provided. The tabletop is made of low radiation absorption, waterproof material. Longitudinal movement of Table Top is 50cm and Transverse movement is 20cm. Auto click stop at centre position. Electro magnetic for Table Top locking. Compression Band is Provided.

VBS

Vertical Bucky Stand with moving Grid of Ratio 8:1, 85 lines. The Bucky moves up & down & are equipped with a stainless steel cassette. This stand is floor mounted type & can accommodate cassettes up to  $14" \times 17"$ .

Country of Origin: USA/Europe/Japan

Note:

Clause No.2 of bid document (Instruction to Bidder) is also modified as under:

Registration of Pakistan Nuclear Regulatory Authority (PNRA) must be attached by Authorized dealer or Sub-Distributor, without registration documentary proof bidders shall be disqualified.

(NUSRAT HUSSAIN MANGAN)
INSPECTOR GENERAL OF PRISONS SINDH
CAMPAT KARACHI