OFFICE OF THE DISTRICT HEALTH OFFICER UMERKOT

TENDER FOR PURHCASE OF MACHINARY INSTRUMENTS/EQUIPMENT/FURNITURE/FIXTURE /BEDDING LINEN FOR UP-GRADATION OF BHU MANDHRO-JO-PAR & AHORI FARM TO THE LEVEL OF RURAL HEALTH CENTER MANDHRO-JO-PAR & AHORI FARM FOR THE YEAR 2011-12

Price Rs.1000/- Non-Refundable/Transferable

Tender inquiry No.01

Due on 16-05-2012

Time of receipt of Tender 16-05-2012 01.00 PM Time of opening of Tender 16-05-2012 02.00 PM

Offers shall remain open for 90 days from the date of opening. The tenders shall quote their prices inclusive of all duties / taxies / Octroi transpiration etc, and all other expenses on fee delivery to Consignee's end. Price should be quoted in Figures & words both, falling which the offer will be ignored.

Item #	Description of Stores/Specifications	Quantity Required	Rate	Rupees in Figures word on FOR & CIF
<u>FURI</u>	NITURE			
1.	Revolving Chair Main frame made with talhi wood seat & back plastic netted plastic based Stand with spirit polish. Standard size Best quality	20		
2.	Office chairs Made with talhi wood seat & back netted with sprit Polish standard size. Best quality	200		
3.	Office Table Made by sheesham wood with Glass Top and side rack handles, channels locks are best quality finish by spirit polish SIZE: (L)5.0"x(W)3.0x (H)2 ½ Best quality	20		
4.	Office Table Made by sheesham wood with glass top and side rack handles, channels locks are best quality finish by spirit polish SIZE: (L) 4'x (W)2 ½ x(H) 2 ½ Best quality	20		
5.	Almirah Steel almirah 6 x 3 x 18 in 22 gauge with grey Hammered paint with three shelve and lockable door	10		
6.	Examination Coach Main Frame made by 1 ¼ x 1 ¼ M.S pipe 18 gauge with head side Adjustable in synthetic leather of best quality with foam 10 years warranty	10		

	and the Frame is in powder Coating			
	and the Frame is in powder coating			
7.	Ward Screen Main frame made by 1" round pipe covered by parachute curtain Standard size with 2" wheels with grey paint.	4	ļ	
8.	Benches with arms and back rest made of seasoned Talhi wood having 06 legs sitting capacity of three persons	20	0	
9.	Files Cabinets Made with 04 drawers in 22 gauge sheet with internal lock and key finished by spray paint	10	0	
10.	File Rack Made by 2 inch angle in 16 gauge with 03 shelves in 22 gauge Steel sheet finish by spray paint	10	0	
11.	Medicine Rack steel Made by 2 inch angle in 16 gauge 6'x 3'x 1 ½ ' with 04 shelves in 22 gauge finished by spray paint	20	0	
12.	Towel Stand Made by 1 inch round Steel pipe with ramps crammed polish	10	0	
13.	Stool Revolving Revolving Stool Frame by 1 round .Steel pipe in 18 gauge in Powder Coating.	20	0	
14.	Visitor Benches Made by 1 ¼ Square pipe in 16 gauge with Fiber Top frame is finished by Epoxy powder coated	20	0	
MEDIC	AL EQUIPMENTS & INSTRUMENTS		•	
1.	Sponge holding forcep	6		
2.	Hard knife handle size # 3	6		
3.	Hard knife handle size # 4	6		
4.	Dissecting Forceps 6" non treathed	6		
5.	Dissecting Forcep 8" non treathed	6		
6.	Dissecting Forcep treathed	6		
7.	Scissors 7" stainless steel	6		
8.	Mcindo diasecting forcep cuurred small size	6		
9.	Mcindo diasecting forcep cuurred mediem size	6		
10.	Artri Forcep Mosquito 6"	40		
11.	Artri Forcep fine point to nail	12		
12.	Artri Forcep right angle long	12		
13.	Kocher Clamp	24		
14.	Intestinal non crushing clamp	10		

15.	Foyers crushing clamp	24	
16.	Alis tissu forcep 8"	24	
17.	Alis tissu forcep 6 1/2"	24	
18.	Banock tissu forcep long	24	
19.	Banock tissu forcep Mediem	24	
20.	Serren Muller Muscle retractors	10	
21.	Prangs lichs skin retractors	10	
22.	Logan Back retractors	10	
23.	Dovers retractors small size	10	
24.	Dovers retractors Mediem size	8	
25.	Balfour Abdominal retractor	10	
26.	Needle Holder 6"	12	
27.	Needle Holder 7"	12	
28.	Sinues forceps 7" Stenless Steel	12	
29.	Aneurysm needle	6	
30.	Kidney stone removing forcep	6	
31.	Million retractor	6	
32.	Folleys Cathator	50	
33.	Cone clamps Lswammon	4	
34.	Boan Lever	4	
35.	Kuccher Nail Jurmoney different size #1,2,3&4	12	
36.	Boan curate mediem size	8	
37.	Boan curate large size	12	
38.	Instrument Tray 18" x 14" x 1 1/2" Stainless Steel with cover	12	
39.	Kidney tray shapede 8"	20	
40.	Kidney tray shapede 10"	20	
41.	Bowel 8" Diameter SS	20	
42.	Basin 14" Diameter SS	10	
43.	Jug SS 8 pints size	10	
44.	Prove 8"	10	
45.	Needle Suture straight size 4, 8, 14	24	

		Г	T	
46.	Cuscose veginal speculam	6		
47.	Needle Trangular pointed cutting size 4, 8, 14	50		
48.	Saline infusion stand	10		
49.	Instruments Sterlizer 16"	6		
50.	Surgical Dressing Table	4		
51.	Dressing Trolley	4		
52.	Set of dressing instruments	2		
53.	Oxygen Cylinder 240 cft (BOC) with flow meter jumboo + meter regulator	4		
54.	Nitreour Oxide cylinders bulk	2		
55.	Dressing Drums	6		
56.	Lumber Puncture Needle	10		
57.	Diathermy Machine Surgical Diathermy 400W Microprocessor digital technology. Mono polar and bipolar cut and coagulation. Seven different types of current Pure, blend I, blend II, blend III, bipolar, spray and contact. Patient return electrode monitoring. 400W maximum out put. Two modes of bi polar coagulation (99 Watts maximum power) and soft coagulation (50 Watts maximum power). Memory function as standard. Pure cut 400W at 500ohms. Blend I: 230W at 300 ohm, Blend II: 180W at 300 ohms, Blend III: 120W at 300 ohms. Contact coagulation: 100W at 300 ohms. Spray coagulation: 80W at 500 ohms. Biopolar coagulation: 99W at 100 ohms. 50 W at 100 ohm . Main frequency 400,500,800KHz +/- 10%. Repetition rate: 20,33KHz +/- 10%. High frequency leakage current: less than 150mA. Low frequency leakage current: patient leads to Ground: Less than 0.01mA, chassis to ground: Less than 0.1mA. Unit complete with: bipolar forceps: reusable bipolar forceps cable. Reusable mono polar handle with cable. Reusable twin button handle with cable. Electrodes . double foot switch. Single foot switch. Disposable dual return plate. Reusable return plate cable. Reusable metal plate with cable. (EEC/Korea/USA/Japan)	2		
58.	ECG Machine 3-channel LCD display 58 mm printouts Battery & mains powered Portable Auto-adaptive filters for outstanding signal quality Loose leads indicator Auto, manual and user-defined profiles Alpha-numeric keyboard Pacemaker detection Display: Graphic display	2		

				ī	T	
	Screen Resolution		128			
	× 64					
	Keyboard	_ 1	:			
	combined alphanumeric and functiona	aı	_			
	Electro connect control indication of connect of each electrod	_				
	Interference	Е				
	RS232, USB reduction		•			
	Printer:					
	Paper width (mm)		: 58			
	Paper type		: roll			
		5, 10,				
	50	. 5, 10,	25,			
	Signal Processing					
	Number of channels		: 1/3			
	Number of leads		: 12			
	Displayed leads		: 1			
	Printed leads		: 1/1,			
	3		, .,			
	Transmission in automatic mode					
	real-time, synchronic		-			
	· · ·	yes				
	Sensitivity (mm/mV)	, , 55	: 2.5,			
	5, 10, 20		,			
	Stored records (10-sec long strips)	6				
	Long ECG recording 1 lead /	. •				
	2 leads (min)		:			
	9/no					
	Digital Filters					
	Adaptable mains filter (Hz)		: 50–			
	60					
	Muscle tremor filters (Hz)		: 35,			
	25		,			
	Baseline Filter (Hz)Automatic	0.05 (3.2			
	s), 0.11 (1.5 s),					
		0.	25			
	(0.6 s), 0.50 (0.3 s),1.50 (0.1 s)					
	UK/USA/EEC					
	Operation Table					
	The operating tables are made of high	h-grade	9			
	stainless steel. Additionally electro-po					
	surfaces provide durability, easy clear	ning ar	ıd			
	disinfection.					
	Ergonomic upholsteries and easy ope					
	complete the design and support fund	ctionalit	У			
	and comfort of patients					
	Continuous X-ray tunnel from head to					
	Lateral guide rails for attachment of	access	ories,			
	stainless steel (25x10mm)					
	Driveability by 2 lockable and 2 direct	ional d	ouble	_		
59.	castors, ø 100mm			2		
	Height adjustment by foot operated hy	ydrauli	2			
	pump from 730 up to 980 mm					
	Manual, gas spring supported Trende		g			
	,	+30°	- 000			
	Manual, gas spring supported lateral	•				
	Manual, gas spring supported adjustn	nent of	pack			
	rest from -40° up to+70°					
	Adjustment to flex /reflex position					
	Weight of the table: 120kg	nm !!	ojah <u>t</u>			
	Floor space required:(I x w) 910x510r	шп, Н	eigni			
1	adjustment: 730 - 980 mm	e∩° La	toral			
<u> </u>	Trendelenburg adjustment: -30°/ +3	o∪ , ∟a	ı c ıal			

M M W CC TI	tilt -20°/+20° tack rest adjustment: -40°/+70° tack rest adjustment: -40°/-70° tack rest adjus		
M W CC TI	Mobile O.T Light Multi –Purpose application for surgery With 205mm reflector with 21 layers special coating which eliminates 90% Red Ray (Hot Ray) The optical filter Glass Filtered 90% With 400mm deep illumination The halogen bulb with comfortable high LUX and		
60. La Ri Ir lu C ap	amp Head Dimension : D 300mm deflector Dimension : D 205mm ntensity (IM Distance) : 0 - 35,000		
Si m Hi isi (h lig Ti D by Ac Si in bu	peration Theater light ceiling type special design for arm balance and cupola hakes the maneuver easy and stable ligh-tech polygon reflector and a-class heat- colation glasses which eliminate the Red-ray not ray), and reflect the low temperature nature ght rue color temperature 4300k, not by coloring rual control system by infrared remote control, or y control panel on cupola djustable illumination from 0 - 100% by both control system special design of 1 main bulb and 1 spare bulbs of cupola with auto switch system to avoid The ulb damage during usage When spare bulb was used, the system will alarm		
61. illu 61. illu 5t La La Ri In Ci Di Bi	ne beep per minute, the beep alarm can Be topped by push the mute-key With memorial function for previous stage of lumination betachable handle can be sterilized by steam terilizer amp no 1pc amp dia(Single head) 62cm teflector Polygon Reflector ntensity(Single head) 110,000LUX color temp 4300°k± 200 tri 93± 3 tocus Range 60 - 180cm tepth of light 70cm tello specs Halogen/24v/150 W tello qty(Each head) Main 1/spare 1 tection radius 170cm	2	
62. M	lead elevation 105cm lower AC100 - 240v Korea/Taiwan/Malaysia Inesthesia lachine with Ventilator Integrated Touch Screen Display for Oxygen	2	

monitor 3.5" Color display Adult Pediatric and neonatal Modes State of the art ergonomic design Top shelf maximum top shelf loading: 35kg Three drawer unit CO2 absorber is autoclave able Three gas machine with a two station selectateo® backbar with up to four cylinder yokes The Oxygen flush is mounted next to the common gas outlet and is recessed for safety Two Vaporizer Connection and supplied with any one vaporizer Vertical Tee Slot mounting System Common gas outlet ISO 22 mm male taper and 15mm female with 90" swivel Pipe line input DISS Cylinder Yokes: up to Four Oxygen Failure device: Nitrous Cuts out with low oxygen Failure device: Nitrous Cuts out with low oxygen failure device: Nitrous Whistle sounds prior to nitrous cut out. Oxygen failure alarm Nitrous Whistle sounds prior to nitrous cut out. Oxygen failure alarm Nitrous Whistle sounds prior to nitrous cut out. Oxygen failure device: Nitrous Cuts out with Normaximum available On/ Off switch mounted blow flow meter bank Mechanical anti hypoxic device Gear driver with minimum 25% Oxygen Concentration Oxygen Flow Range (Dual Tube) 0-1000ml and 1-10 liters Nitrous oxide flow range (dual tube) 0-1000ml and 1-10 liters Nitrous oxide flow range (dual tube) 0-1000ml and 1-10 liters Ouick release manometer Anesthesia Ventilator Inspiratory time 0.25 – 3.0 seconds , Expiratory time 0.5 – 6.0 seconds, Flow rate 0.1 – 1.0 liters per second ,!: E Ratio Derived from inspiratory and expiratory time, Tidal volume 5mi – 1600ml Adult Bellows ,25ml – 300ml Pediatric Bellows Supply Pressure 45-100PSI (310-700 KPA) ,Airway Pressure Gauge 20-100cm H2O Range Adjustable low pressure alarm 20-80 cm H2O, Adjustable high pressure alarm 10-70 cm H2O External power supply 90-264 volts A.C. Battery Backup 12 hours minimum USAUK/EEC/ JAPAN Labour Operation Table 63. Electric hydraulic control for elevation, break back change and trendelebrug				
Supply Pressure 45-100PSI (310-700 KPA) ,Airway Pressure Gauge 20-100cm H2O Range Adjustable low pressure alarm 20-80 cm H2O,Adjustable high pressure alarm 10-70 cm H2O External power supply 90- 264 volts A.C, Battery Backup 12 hours minimum USA/UK/EEC/ JAPAN Labour Operation Table 63. Electric hydraulic control for elevation, break 2		Adult Pediatric and neonatal Modes State of the art ergonomic design Top shelf maximum top shelf loading: 35kg Three drawer unit CO2 absorber is autoclave able Three gas machine with a two station selectatec® backbar with up to four cylinder yokes The Oxygen flush is mounted next to the common gas outlet and is recessed for safety Two Vaporizer Connection and supplied with any one vaporizer Vertical Tee Slot mounting System Common gas outlet ISO 22 mm male taper and 15mm female with 90° swivel Pipe line input DISS Cylinder Yokes: up to Four Oxygen Failure device: Nitrous Cuts out with low oxygen pressure (Air/ Oxygen remain) Oxygen failure alarm Nitrous Whistle sounds prior to nitrous cut out. Oxygen and Air High pressure DISS outlet two maximum available On/ Off switch mounted blow flow meter bank shrouded Secondary regulator for flow meter bank Mechanical anti hypoxic device Gear driver with minimum 25% Oxygen Concentration Oxygen Flow Range (Dual Tube) 0-1000ml and 1- 10 liters Nitrous oxide flow range (dual tube) 0-1000ml and 1-10 Liters Quick release manometer Anesthesia Ventilator Inspiratory time 0.25 – 3.0 seconds, Expiratory time 0.5 – 6.0 seconds, Flow rate 0.1 – 1.0 liters per second,!: E Ratio Derived from inspiratory and expiratory time, Tidal volume 5ml – 1600ml Adult Bellows ,25ml –		
H2O,Adjustable high pressure alarm 10-70 cm H2O External power supply 90- 264 volts A.C, Battery Backup 12 hours minimum USA/UK/EEC/ JAPAN Labour Operation Table 63. Electric hydraulic control for elevation, break 2		300ml Pediatric Bellows Supply Pressure 45-100PSI (310-700 KPA) ,Airway Pressure Gauge 20-100cm H2O Range		
Labour Operation Table 63. Electric hydraulic control for elevation, break 2		H2O,Adjustable high pressure alarm 10-70 cm H2O External power supply 90- 264 volts A.C,		
I had a share a seed the red also with	63.	Labour Operation Table Electric hydraulic control for elevation, break	2	

Sitting and lying position is suitable for delivery. It can be an operation table immediately without moving The Auxiliary table is canceled under the tabletop and it is easy to extend and elevate The foot controller is water proof and 24V control 3- IN-1 Multi Function Table as obstetric table, Gynecological operation table & examination table Tabletop : 60x130 cm Tabletop with Auxiliary Table : 60x180 cm Evevation : 66-96 cm Trendelenburg : +25,10 Back Up /Down : +70-0 Power Supply : AC 110 V / 230V With Standard Accessories: Pillow : 1 Pc. Arm boards : 2 Pcs. Mattress : 1 Pc. Water proof Seat Cover : 1 Pc Waist Side Handles : 2 Pcs. Leg crutches : 2 Sets Auxiliary Table : 1 Pc. Slpoing pan (with Filter) : 1 Pc. Foot Controller : 1 Set. Power Cord : 1 Pc. Korea /Taiwan/Malaysia Auto Clave Horizontal Semi-Automatic Sterilizer With Dry and re dry function auto exhaust With low water indicator With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121 (1.05KG/CM) .134C(2.07KG/CM2) Design Temperature 1210 (5.05KG/CM) Filling Water Manual
moving The Auxiliary table is canceled under the tabletop and it is easy to extend and elevate The foot controller is water proof and 24V control 3-IN-1 Multi Function Table as obstetric table, Gynecological operation table & examination table Tabletop : 60x130 cm Tabletop with Auxiliary Table : 60x180 cm Evevation : 66-96 cm Trendelenburg : +25, -10 Back Up /Down : +70-0 Power Supply : AC 110 V / 230V With Standard Accessories: Pillow : 1 Pc. Arm boards : 2 Pcs. Mattress : 1 Pc. Water proof Seat Cover : 1 Pc Waist Side Handles : 2 Pcs. Leg crutches : 2 Sets Auxiliary Table : 1 Pc. Slpoing pan (with Filter) : 1 Pc. Foot Controller : 1 Set. Power Cord : 1 Pc. Korea /Taiwan/Malaysia Auto Clave Horizontal Semi-Automatic Sterilizer With Dry and re dry function auto exhaust With low water indicator With auto exhaust function With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Diameter 121C(1.05KG/CM) .134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
The Auxiliary table is canceled under the tabletop and it is easy to extend and elevate The foot controller is water proof and 24V control 3-IN-1 Multi Function Table as obstetric table, Gynecological operation table & examination table Tabletop : 60x130 cm Tabletop with Auxiliary Table : 60x180 cm Evevation : 66-96 cm Trendelenburg : +25, -10 Back Up /Down : +70-0 Power Supply : AC 110 V / 230V With Standard Accessories: Pillow : 1 Pc. Arm boards : 2 Pcs. Mattress : 1 Pc. Water proof Seat Cover : 1 Pc Waist Side Handles : 2 Pcs. Leg crutches Auxiliary Table : 1 Pc. Slpoing pan (with Filter) : 1 Pc. Slpoing pan (with Filter) : 1 Pc. Foot Controller : 1 Set. Power Cord : 1 Pc. Korea /Talwan/Malaysia Auto Clave Horizontal Semi-Automatic Sterilizer With Dry and re dry function auto exhaust With low water indicator With auto exhaust function With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121C(1.05KG/CM) .134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
The Auxiliary table is canceled under the tabletop and it is easy to extend and elevate The foot controller is water proof and 24V control 3-IN-1 Multi Function Table as obstetric table, Gynecological operation table & examination table Tabletop : 60x130 cm Tabletop with Auxiliary Table : 60x180 cm Evevation : 66-96 cm Trendelenburg : +25, -10 Back Up /Down : +70-0 Power Supply : AC 110 V / 230V With Standard Accessories: Pillow : 1 Pc. Arm boards : 2 Pcs. Mattress : 1 Pc. Water proof Seat Cover : 1 Pc Waist Side Handles : 2 Pcs. Leg crutches Auxiliary Table : 1 Pc. Slpoing pan (with Filter) : 1 Pc. Slpoing pan (with Filter) : 1 Pc. Foot Controller : 1 Set. Power Cord : 1 Pc. Korea /Talwan/Malaysia Auto Clave Horizontal Semi-Automatic Sterilizer With Dry and re dry function auto exhaust With low water indicator With auto exhaust function With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121C(1.05KG/CM) .134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
tabletop and it is easy to extend and elevate The foot controller is water proof and 24V control 3- IN -1 Multi Function Table as obstetric table, Gynecological operation table & examination table Tabletop : 60x130 cm Tabletop with Auxiliary Table : 60x180 cm Evevation : 66-96 cm Trendelenburg : +25,10 Back Up /Down : +70-0 Power Supply : AC 110 V / 230V With Standard Accessories: Pillow : 1 Pc. Arm boards : 2 Pcs. Mattress : 1 Pc. Water proof Seat Cover : 1 Pc Water proof Seat Cover : 1 Pc Waits Side Handles : 2 Pcs. Leg crutches : 2 Sets Auxiliary Table : 1 Pc. Sippoing pan (with Filter) : 1 Pc. Foot Controller : 1 Set. Power Cord : 1 Pc. Korea /Taiwan/Malaysia Auto Clave Horizontal Semi-Automatic Sterilizer With Dry and re dry function auto exhaust With low water indicator With auto exhaust function With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121C(1.05KG/CM) .134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
The foot controller is water proof and 24V control 3- IN -1 Multi Function Table as obstetric table, Gynecological operation table & examination table Tabletop : 60x130 cm Tabletop with Auxiliary Table : 60x180 cm Evevation : 66-96 cm Trendelenburg : +25,10 Back Up /Down : +70 -0 Power Supply : AC 110 V / 230V With Standard Accessories: Pillow : 1 Pc. Arm boards : 2 Pcs. Mattress : 1 Pc. Water proof Seat Cover : 1 Pc Waist Side Handles : 2 Pcs. Leg crutches : 2 Sets Auxiliary Table : 1 Pc. Slpoing pan (with Filter) : 1 Pc. Slpoing pan (with Filter) : 1 Pc. Foot Controller : 1 Set. Power Cord : 1 Pc. Korea /Taiwan/Malaysia Auto Clave Horizontal Semi-Automatic Sterilizer With Dry and re dry function auto exhaust With low water indicator With auto exhaust function With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Capacity 40 Liters Sterilization Temperature 121°C(1.05KG/CM) .134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
control 3- IN -1 Multi Function Table as obstetric table, Gynecological operation table & examination table Tabletop : 60x130 cm Tabletop with Auxiliary Table : 60x180 cm Evevation : 66-96 cm Trendelenburg : +25, -10 Back Up /Down : +70 -0 Power Supply : AC 110 V / 230V With Standard Accessories: Pillow : 1 Pc. Arm boards : 2 Pcs. Mattress : 1 Pc. Water proof Seat Cover : 1 Pc Waist Side Handles : 2 Pcs. Leg crutches : 2 Sets Auxiliary Table : 1 Pc. Slpoing pan (with Filter) : 1 Pc. Foot Controller : 1 Set. Power Cord Fawan/Malaysia Auto Clave Horizontal Semi-Automatic Sterilizer With Dry and re dry function auto exhaust With low water indicator With auto exhaust function With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Litlers Sterilization Temperature 121°C (1.05KG/CM) 1,134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
3- IN -1 Multi Function Table as obstetric table, Gynecological operation table & examination table Tabletop : 60x130 cm Tabletop with Auxiliary Table : 60x180 cm Evevation : 66-96 cm Trendelenburg : +25, -10 Back Up /Down : +70 -0 Power Supply : AC 110 V / 230V With Standard Accessories: Pillow : 1 Pc. Arm boards : 2 Pcs. Mattress : 1 Pc. Water proof Seat Cover : 1 Pc Waist Side Handles : 2 Pcs. Leg crutches : 2 Sets Auxiliary Table : 1 Pc. Slpoing pan (with Filter) : 1 Pc. Slpoing pan (with Filter) : 1 Pc. Foot Controller : 1 Set. Power Cord : 1 Pc. Korea /Taiwan/Malaysia Auto Clave Horizontal Semi-Automatic Sterilizer With Dry and re dry function auto exhaust With low water indicator With auto exhaust function With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121C(1.05KG/CM) .134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
Gynecological operation table & examination table Tabletop : 60x130 cm Tabletop with Auxiliary Table : 60x180 cm Evevation : 66-96 cm Trendelenburg : +25,10 Back Up /Down : +70 -0 Power Supply : AC 110 V / 230V With Standard Accessories: Pillow : 1 Pc. Arm boards : 2 Pcs. Mattress : 1 Pc. Water proof Seat Cover : 1 Pc. Waist Side Handles : 2 Pcs. Leg crutches : 2 Sets Auxiliary Table : 1 Pc. Slpoing pan (with Filter) : 1 Pc. Slpoing pan (with Filter) : 1 Pc. Foot Controller : 1 Set. Power Cord : 1 Pc. Korea /Taiwan/Malaysia Auto Clave Horizontal Semi-Automatic Sterilizer With Dry and re dry function auto exhaust With low water indicator With auto exhaust function With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121°C(1.05KG/CM) ,134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
table Tabletop Tabletop :: 60x130 cm Tabletop with Auxiliary Table :: 60x180 cm Evevation :: 66-96 cm Trendelenburg :: +25,10 Back Up /Down :: +70 -0 Power Supply :: AC 110 V / 230V With Standard Accessories: Pillow :: 1 Pc. Arm boards :: 2 Pcs. Mattress :: 1 Pc. Water proof Seat Cover :: 1 Pc Waist Side Handles :: 2 Pcs. Leg crutches :: 2 Sets Auxiliary Table :: 1 Pc. Slpoing pan (with Filter) :: 1 Pc. Slpoing pan (with Filter) :: 1 Pc. Foot Controller :: 1 Set. Power Cord :: 1 Pc. Korea /Taiwan/Malaysia Auto Clave Horizontal Semi-Automatic Sterilizer With Dry and re dry function auto exhaust With low water indicator With auto exhaust function With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121C(1.05KG/CM) ,134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
Tabletop : 60x130 cm Tabletop with Auxiliary Table : 60x180 cm Evevation : 66-96 cm Trendelenburg : +25, -10 Back Up /Down : +70 -0 Power Supply : AC 110 V / 230V With Standard Accessories: Pillow : 1 Pc. Arm boards : 2 Pcs. Mattress : 1 Pc. Water proof Seat Cover : 1 Pc Waist Side Handles : 2 Pcs. Leg crutches : 2 Sets Auxiliary Table : 1 Pc. Slpoing pan (with Filter) : 1 Pc. Foot Controller : 1 Set. Power Cord : 1 Pc. Korea /Taiwan/Malaysia Auto Clave Horizontal Semi-Automatic Sterilizer With Dry and re dry function auto exhaust With low water indicator With auto exhaust function With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121°C(1.05KG/CM) ,134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
cm Tabletop with Auxiliary Table: 60x180 cm Evevation : 66-96 cm Trendelenburg : +25,10 Back Up /Down : +70 -0 Power Supply : AC 110 V / 230V With Standard Accessories: Pillow : 1 Pc. Arm boards : 2 Pcs. Mattress : 1 Pc. Water proof Seat Cover : 1 Pc. Waits Side Handles : 2 Pcs. Leg crutches : 2 Sets Auxiliary Table : 1 Pc. Slpoing pan (with Filter) : 1 Pc. Slpoing pan (with Filter) : 1 Pc. Foot Controller : 1 Set. Power Cord : 1 Pc. Korea /Taiwan/Malaysia Auto Clave Horizontal Semi-Automatic Sterilizer With Dry and re dry function auto exhaust With low water indicator With auto exhaust function With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121C(1.05KG/CM) ,134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
cm Tabletop with Auxiliary Table: 60x180 cm Evevation : 66-96 cm Trendelenburg : +25,10 Back Up /Down : +70 -0 Power Supply : AC 110 V / 230V With Standard Accessories: Pillow : 1 Pc. Arm boards : 2 Pcs. Mattress : 1 Pc. Water proof Seat Cover : 1 Pc. Waits Side Handles : 2 Pcs. Leg crutches : 2 Sets Auxiliary Table : 1 Pc. Slpoing pan (with Filter) : 1 Pc. Slpoing pan (with Filter) : 1 Pc. Foot Controller : 1 Set. Power Cord : 1 Pc. Korea /Taiwan/Malaysia Auto Clave Horizontal Semi-Automatic Sterilizer With Dry and re dry function auto exhaust With low water indicator With auto exhaust function With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121C(1.05KG/CM) ,134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
Tabletop with Auxiliary Table: 60x180 cm Evevation : 66-96 cm Trendelenburg : +25, -10 Back Up /Down : +70 -0 Power Supply : AC 110 V / 230V With Standard Accessories: Pillow :1 Pc. Arm boards :2 Pcs. Mattress :1 Pc. Water proof Seat Cover :1 Pc Waist Side Handles :2 Pcs. Leg crutches :2 Sets Auxiliary Table :1 Pc. Slpoing pan (with Filter) :1 Pc. Foot Controller :1 Set. Power Cord :1 Pc. Korea Taiwan/Malaysia Auto Clave Horizontal Semi-Automatic Sterilizer With Dry and re dry function auto exhaust With low water indicator With auto exhaust function With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121C(1.05KG/CM) ,134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
Evevation : 66-96 cm Trendelenburg : +25,10 Back Up /Down Power Supply : AC 110 V / 230V With Standard Accessories: Pillow : 1 Pc. Arm boards : 2 Pcs. Mattress : 1 Pc. Water proof Seat Cover : 1 Pc Waist Side Handles : 2 Pcs. Leg crutches : 2 Sets Auxiliary Table : 1 Pc. Slpoing pan (with Filter) : 1 Pc. Foot Controller : 1 Pc. Foot Controller : 1 Pc. Korea /Taiwan/Malaysia Auto Clave Horizontal Semi-Automatic Sterilizer With Dry and re dry function auto exhaust With low water indicator With auto exhaust function With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121C(1.05KG/CM) , 134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
Trendelenburg : +25, -10 Back Up /Down : +70 -0 Power Supply : AC 110 V / 230V With Standard Accessories: Pillow : 1 Pc. Arm boards : 2 Pcs. Mattress : 1 Pc. Water proof Seat Cover : 1 Pc Waist Side Handles : 2 Pcs. Leg crutches : 2 Sets Auxiliary Table : 1 Pc. Slpoing pan (with Filter) : 1 Pc. Foot Controller : 1 Set. Power Cord : 1 Pc. Korea /Taiwan/Malaysia Auto Clave Horizontal Semi-Automatic Sterilizer With Dry and re dry function auto exhaust With low water indicator With auto exhaust function With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121°C(1.05KG/CM) ,134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
Back Up /Down Power Supply: AC 110 V / 230V With Standard Accessories: Pillow: 1 Pc. Arm boards: 2 Pcs. Mattress: 1 Pc. Water proof Seat Cover: 1 Pc. Waist Side Handles: 2 Pcs. Leg crutches: 2 Sets Auxiliary Table: 1 Pc. Slpoing pan (with Filter): 1 Pc. Slpoing pan (with Filter): 1 Pc. Foot Controller: 1 Set. Power Cord: 1 Pc. Korea /Taiwan/Malaysia Auto Clave Horizontal Semi-Automatic Sterilizer With Dry and re dry function auto exhaust With low water indicator With auto exhaust function With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121C(1.05KG/CM) ,134C(2.07KG/CM2) Design Temperature 140C Filling Water: Manual
Power Supply : AC 110 V / 230V With Standard Accessories: Pillow : 1 Pc. Arm boards : 2 Pcs. Mattress : 1 Pc. Water proof Seat Cover : 1 Pc Waist Side Handles : 2 Pcs. Leg crutches : 2 Sets Auxiliary Table : 1 Pc. Slpoing pan (with Filter) : 1 Pc. Foot Controller : 1 Set. Power Cord : 1 Pc. Korea /Taiwan/Malaysia Auto Clave Horizontal Semi-Automatic Sterilizer With Dry and re dry function auto exhaust With low water indicator With auto exhaust function With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121C(1.05KG/CM) 1,134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
With Standard Accessories: Pillow : 1 Pc. Arm boards : 2 Pcs. Mattress : 1 Pc. Water proof Seat Cover : 1 Pc Waist Side Handles : 2 Pcs. Leg crutches : 2 Sets Auxiliary Table : 1 Pc. Slpoing pan (with Filter) : 1 Pc. Foot Controller : 1 Set. Power Cord : 1 Pc. Korea /Taiwan/Malaysia Auto Clave Horizontal Semi-Automatic Sterilizer With Dry and re dry function auto exhaust With low water indicator With auto exhaust function With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121C(1.05KG/CM) ,134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
Pillow Arm boards Sizer Pcs. Mattress Mattress Water proof Seat Cover Waist Side Handles Leg crutches Leg crutches Leg crutches Leg crutches Slpoing pan (with Filter) Foot Controller Foot Controller Foot Controller Foot Controller Foot Cantroller Foot Controller Foot Co
Pillow Arm boards Sizer Pcs. Mattress Mattress Water proof Seat Cover Waist Side Handles Leg crutches Leg crutches Leg crutches Leg crutches Slpoing pan (with Filter) Foot Controller Foot Controller Foot Controller Foot Controller Foot Cantroller Foot Controller Foot Co
Arm boards : 2 Pcs. Mattress : 1 Pc. Water proof Seat Cover : 1 Pc Waist Side Handles : 2 Pcs. Leg crutches : 2 Sets Auxiliary Table : 1 Pc. Slpoing pan (with Filter) : 1 Pc. Foot Controller : 1 Set. Power Cord : 1 Pc. Korea /Taiwan/Malaysia Auto Clave Horizontal Semi-Automatic Sterilizer With Dry and re dry function auto exhaust With low water indicator With auto exhaust function With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121C(1.05KG/CM) J.134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
Arm boards : 2 Pcs. Mattress : 1 Pc. Water proof Seat Cover : 1 Pc Waist Side Handles : 2 Pcs. Leg crutches : 2 Sets Auxiliary Table : 1 Pc. Slpoing pan (with Filter) : 1 Pc. Foot Controller : 1 Set. Power Cord : 1 Pc. Korea /Taiwan/Malaysia Auto Clave Horizontal Semi-Automatic Sterilizer With Dry and re dry function auto exhaust With low water indicator With auto exhaust function With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121C(1.05KG/CM) J.134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
Mattress : 1 Pc. Water proof Seat Cover : 1 Pc Waist Side Handles : 2 Pcs. Leg crutches : 2 Sets Auxiliary Table : 1 Pc. Slpoing pan (with Filter) : 1 Pc. Foot Controller : 1 Set. Power Cord : 1 Pc. Korea /Taiwan/Malaysia Auto Clave Horizontal Semi-Automatic Sterilizer With Dry and re dry function auto exhaust With low water indicator With auto exhaust function With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121C(1.05KG/CM) ,134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
Water proof Seat Cover Waist Side Handles 2 Pcs. Leg crutches 3 2 Sets Auxiliary Table 3 1 Pc. Sipoing pan (with Filter) 4 1 Pc. Foot Controller 5 1 Pc. Foot Controller 7 1 Set. Power Cord 8 Auto Clave Horizontal Semi-Automatic Sterilizer With Dry and re dry function auto exhaust With low water indicator With auto exhaust function With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121C(1.05KG/CM) ,134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
Waist Side Handles : 2 Pcs. Leg crutches : 2 Sets Auxiliary Table : 1 Pc. Slpoing pan (with Filter) : 1 Pc. Foot Controller : 1 Set. Power Cord : 1 Pc. Korea /Taiwan/Malaysia Auto Clave Horizontal Semi-Automatic Sterilizer With Dry and re dry function auto exhaust With low water indicator With auto exhaust function With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121C(1.05KG/CM) ,134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
Leg crutches : 2 Sets Auxiliary Table : 1 Pc. Slpoing pan (with Filter) : 1 Pc. Foot Controller : 1 Set. Power Cord : 1 Pc. Korea /Taiwan/Malaysia Auto Clave Horizontal Semi-Automatic Sterilizer With Dry and re dry function auto exhaust With low water indicator With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121C(1.05KG/CM) ,134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
Auxiliary Table : 1 Pc. Slpoing pan (with Filter) : 1 Pc. Foot Controller : 1 Set. Power Cord : 1 Pc. Korea /Taiwan/Malaysia Auto Clave Horizontal Semi-Automatic Sterilizer With Dry and re dry function auto exhaust With low water indicator With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121C(1.05KG/CM) ,134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
Slpoing pan (with Filter) : 1 Pc. Foot Controller : 1 Set. Power Cord : 1 Pc. Korea /Taiwan/Malaysia Auto Clave Horizontal Semi-Automatic Sterilizer With Dry and re dry function auto exhaust With low water indicator With auto exhaust function With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121C(1.05KG/CM) ,134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
Foot Controller : 1 Set. Power Cord : 1 Pc. Korea /Taiwan/Malaysia Auto Clave Horizontal Semi-Automatic Sterilizer With Dry and re dry function auto exhaust With low water indicator With auto exhaust function With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121C(1.05KG/CM) ,134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
Foot Controller : 1 Set. Power Cord : 1 Pc. Korea /Taiwan/Malaysia Auto Clave Horizontal Semi-Automatic Sterilizer With Dry and re dry function auto exhaust With low water indicator With auto exhaust function With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121C(1.05KG/CM) ,134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
Power Cord Korea /Taiwan/Malaysia Auto Clave Horizontal Semi-Automatic Sterilizer With Dry and re dry function auto exhaust With low water indicator With auto exhaust function With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121C(1.05KG/CM) ,134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
Auto Clave Horizontal Semi-Automatic Sterilizer With Dry and re dry function auto exhaust With low water indicator With auto exhaust function With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121C(1.05KG/CM) ,134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
Auto Clave Horizontal Semi-Automatic Sterilizer With Dry and re dry function auto exhaust With low water indicator With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121C(1.05KG/CM) ,134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
Horizontal Semi-Automatic Sterilizer With Dry and re dry function auto exhaust With low water indicator With auto exhaust function With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121C(1.05KG/CM) ,134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
With Dry and re dry function auto exhaust With low water indicator With auto exhaust function With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121C(1.05KG/CM) ,134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
With low water indicator With auto exhaust function With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121C(1.05KG/CM) ,134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
With auto exhaust function With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121C(1.05KG/CM) ,134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
With sterilization temperature 121°C and 134°C both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121C(1.05KG/CM) ,134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
both Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121C(1.05KG/CM) ,134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
Door close knob is 90° close/open design light and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121C(1.05KG/CM),134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121C(1.05KG/CM) ,134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
and convenient for operation Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121C(1.05KG/CM) ,134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
Chamber Diameter 315MM Chamber Capacity 40 Liters Sterilization Temperature 121C(1.05KG/CM) ,134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
Chamber Capacity 40 Liters Sterilization Temperature 121C(1.05KG/CM) ,134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
Sterilization Temperature 121C(1.05KG/CM) ,134C(2.07KG/CM2) Design Temperature 140C Filling Water Manual
64.
Design Temperature 140C Filling Water Manual
Filling Water Manual
Dry Function yes
Power Consumption 3.0KW
Voltage /Frequency 230V /50-60HZ
Voltage /1 Toquettoy 200 V /00-00112
Standard Assessarias
Standard Accessories
SUS# 304 Stainless steel sterilization box x 1
SUS# 304 Stainless steel heater cover x 1
Made : Korea / Taiwan /
Malaysia
100 mA Mobile X-Ray System
Articulated tube head arms to position the tube
head for all possible radiographic positions.
Fully sounder helenged tube band for some of
Fully counter balanced tube head for ease of
Fully counter balanced tube head for ease of handing. Soft touch switch panel.

		T	_	1
	Power supply : 11/230V), 50/60Hz			
	Voltage/ frequency available A.C, 1 phase			
	Power supply : 11/230V),			
	50/60Hz			
	Voltage/ frequency available A.C, 1 phase			
	Type of Generator :2 Pulse, Full Wa	ive		
	Rectified Double Tank	.,,		
	·			
	Focal Spot : Single Focus			
	Tube Head Type : Shell Type			
	H.V. Cable : Pair of 2.5 mts.			
	Radiographic mA :25,50 & 100mA			
	Radiographic kvp :45 to 100K\	/P.		
	Step of 5KV			
	Timer (Electronic) : 0.04 to 8 Sec. (24		
	Steps)	,		
	Digital Displays : mA, mAs & KVF)		
	Eightar Dioplays : IIII I, III I o a TVI			
	Korea /Taiwan/India			
-	Dental Unit alongwith all accessories			
66.	Korea/ Taiwan & India			
	Ultrasound Machine			
	System Configuration			
	Console with foldable keyboard			
	Probe/Gel holder (Removable)			
	Probe (user selectable)			
	Power cord			
	Probe pad			
	Gel bottle			
	Scanning			
	Convex, Micro Convex, Linear electronic			
	scanning.			
	Electrical power			
	Power supply			
	220/240V-50/60 Hz, 170 VA Max,			
	Single phase			
	100/115V-50/60Hz, 140 VA Max,			
	· · · · · · · · · · · · · · · · · · ·			
	Single Phase			
	Environmental requirements			
67.	Operating: 10 to 40 degree C at 30 to 75 %	2		
	relative humidity			
	Storage: -10 to 60 degrees C at 30 to 90%			
	relative humidity.			
	Transport: -40 to 60 degrees C at 30 to 90%			
	relative humidity.			
	Display modes			
	B, B/M, M-Mode Dual B-Mode			
	PROBE			
	Applications: OBG, Abdomen, Cardiology			
	Frequency: 3.5 MHz & 7.5 MHz			
	Field of View: 68°			
	ROC: 50mm			
	Biopsy Guide: Available			
	Diopoy Guide. Available			
	STANDARD ACCESSORIES:			
	Probe 3.5 MHz Convex & 7.5 MHz			
	Stabilizer			
	Trolley (Local Made)			
•	i i i onoy (Eoodi ividao)	1		1
	UK/USA/EEC	l		

ENT INS	STRUMENTS		
1.	Ibraham Tonsil knife	2	
2.	Forceps	2	
3.	Alac Nasal Dialators	2	
4.	Agnow Myringopome	2	
5.	Trocars & Cannula	4	
6.	Nasal Spanula Speculum	10	
7.	Arti Forcep	20	
8.	Mouth Gag	2	
9.	Aural Curators	2	
10.	Aural Forceps	2	
11.	Auriscope	2	
12.	Baker Traccheostomy tubes	12	
13.	Ballanger Samar	2	
14.	Ballanger Cartillage knives	2	
15.	Bossvic Tonsil retractor	2	
16.	Turbinocotomy scissors	2	
17.	Birket Tonsil Arty forcep	8	
18.	Boyd Tonsil Scissors	2	
19.	Suction Tube	4	
20.	Tonsil holding forcep	2	
21.	Tuning Forks set	2	
22.	Politzer Bag	2	
23.	Tonsil Snare	2	
24.	Bur Stand	2	
25.	Knife Handles	2	
26.	Nasal dressing forcep	2	
27.	Scissors Dressing	2	
28.	Head Light with Adopters	2	
20. 29.	Diasection Forcep		
29.	•	2	

30.	Tongue Plates Tonsils	6	
31.	Dressing Trolley	2	
32.	Eustachian Cathetors	2	
33.	Eve Tonsil snares	2	
34.	Face Shielts	2	
35.	Rasp	2	
36.	Punch Forceps	2	
37.	Farhan Rhinoplastiy scissor	2	
38.	Foster Ballenger sputum forcep	2	
39.	Arti Forcep	10	
40.	Freerchasel	2	
41.	Seprator and illevator	2	
42.	Gage mouth	2	
43.	Gage suspension apperatus	2	
44.	Osteotomos	2	
45.	Skin Hooks	2	
46.	Nasal Snare	2	
47.	Grunwals Turbinate Forceps	2	
48.	Nasal Gauge	2	
49.	Gwyano Evans Tonsil Diasector	2	
50.	Retractors	2	
51.	Nasal dressing forcep	2	
52.	Sterlising Box	2	
53.	Instrument Cabinet	4	
54.	Insulated Nasal Specula	2	
55.	Jankina Chisels	4	
56.	Jabson Probe	4	
57.	Tansil Disector	2	
58.	Kidney shape dressin tray	4	
59.	Back Tongue depressor	6	
60.	Muck Tansil Forcep	2	

61.	Mouth Gag with Tongue holdin forcep	2	
62.	Stand for Mouth Gag	2	
63.	Tonsilor Arti Forcep	6	
64.	Tonsilor Knife forcep	2	
65.	Freer Diasector	2	
66.	Freer Forceps	2	
67.	Freer Snare	2	
68.	Freer Needle	2	
69.	Wilson Artery forcep	2	
70.	Thread carier	2	
71.	Tonsilar Scissors	2	
72.	Nasal Spanula Short Blade	6	
73.	Nasal Spanula Long Blade	2	
74.	Nasal Packing Forcep	4	
75.	Luda Forcep	2	
76.	Doubble Action Bano Punch	2	
77.	Hammer	2	
78.	Chiseal Nasal (All Size)	4	
79.	Post Aural Mastoid retractor	2	
80.	End Aural Mastoid retractor	2	
81.	Paristone Elevator	2	
82.	Ear Speculum (All Size)	10	
83.	Ear Speculum with Handle	2	
84.	Electric Cautary	10	
85.	Cautary points	10	
86.	Biopsy Forcep	6	
GYNAE	COLOGICAL INSTRUMENTS		
1.	Sponge holding forcep 7" Straight Box joint foor stors	12	
2.	Volsollum forceps teals 9 1/2" Teeth SS Box joint	6	
3.	Mayo Scissors 8" SS	4	
-			

Anwards speculum (Weight)	4		
Female Matel Cathetor	10		
Dialetor set Heger in a box	2		
Allis tisu forcep	50		
Curved Artery forcep size 9"	24		
Straight Artery forcep 9"	24		
Episitomy scissors	4		
Mays Abdominal Bivalve retractor	6		
Mays Abdominal Trivalve retractor	6		
Abdominal Dialator retractor set round handle 12" & 15"	4		
Uterian Scissors straight 9"	4		
Uterian Scissors Curved 9"	4		
Operating revolving Steel	6		
Uterian forceps	4		
Cuscose veginal speculam	4		
Towel Clips	96		
D & C Set Complete in box	4		
Uterian Clamp	4		
Vacum Extractor	2		
ATORY EQUIPMENTS			
Laboratory Table	2		
Microscope Binocular with 02 objectives complete with cabinet Specifications: Binocular head inclined 45° and 360° rotating. Eyepiece: Widefield WF10x (FN18) (paired) Objective: Plan achromatic PL4x/0.10, achromatic A10x/0.25, A40x/0.65 (spring), A 100x/1.25 (oil. spring)			
	Female Matel Cathetor Dialetor set Heger in a box Allis tisu forcep Curved Artery forcep size 9" Straight Artery forcep 9" Episitomy scissors Mays Abdominal Bivalve retractor Mays Abdominal Trivalve retractor Abdominal Dialator retractor set round handle 12" & 15" Uterian Scissors straight 9" Uterian Scissors Curved 9" Operating revolving Steel Uterian forceps Cuscose veginal speculam Towel Clips D & C Set Complete in box Uterian Clamp Vacum Extractor ATORY EQUIPMENTS Laboratory Table Microscope Binocular with 02 objectives complete with cabinet Specifications: Binocular head inclined 45° and 360° rotating. Eyepiece: Widefield WF10x (FN18) (paired) Objective: Plan achromatic PL4x/0.10, achromatic A10x/0.25, A40x/0.65 (spring), A 100x/1.25 (oil. spring)	Female Matel Cathetor Dialetor set Heger in a box Allis tisu forcep 50 Curved Artery forcep size 9" 24 Straight Artery forcep 9" 24 Episitomy scissors 4 Mays Abdominal Bivalve retractor 6 Mays Abdominal Trivalve retractor Abdominal Dialator retractor set round handle 12" 8 15" Uterian Scissors straight 9" 4 Uterian Scissors Curved 9" 4 Operating revolving Steel 6 Uterian forceps 4 Cuscose veginal speculam 7 owel Clips D & C Set Complete in box 4 Uterian Clamp 4 Vacum Extractor 2 ATORY EQUIPMENTS Laboratory Table Diagraphic Allow (Pilas) Binocular with 02 objectives complete with cabinet Specifications: Binocular head inclined 45° and 360° rotating. Eyepiece: Widefield WF10x (FN18) (paired) Objective: Plan achromatic PL4x/0.10, achromatic A10x/0.25, A40x/0.65 (spring), A	Female Matel Cathetor Dialetor set Heger in a box Allis tisu forcep 50 Curved Artery forcep size 9" Straight Artery forcep 9" Episitomy scissors 4 Mays Abdominal Bivalve retractor Mays Abdominal Trivalve retractor 6 Abdominal Dialator retractor set round handle 12" 4 4 Uterian Scissors straight 9" 4 Uterian Scissors Curved 9" 4 Operating revolving Steel 6 Uterian forceps 4 Cuscose veginal speculam 7 Towel Clips D & C Set Complete in box 4 Uterian Clamp Vacum Extractor ATORY EQUIPMENTS Laboratory Table Microscope Binocular with 02 objectives complete with cabinet Specifications: Binocular head inclined 45° and 360° rotating. Eyepiece: Widefield WF10x (FN18) (paired) Objective: Plan achromatic PL4x/0.10, achromatic A10x/0.25, A40x/0.65 (spring), A 100x/1.25 (oil. spring) Oundruple proposition (hell)

	There is a Constant of the Con	T	l	<u> </u>
	illumination 12V/20W with intensity control Main supply 220-240V VDE Plug CE Germany/USA/Japan			
3.	Reflectron for verious Blood Tests Bechringer Mannhoim Gmbh D-68000 Mannhoin West germany	2		
4.	4. Micro Scope Lamp			
5.	5. Buretta Stand			
6.	Pupette Racks	2		
7.	Centrifuge Machine Speed Range: 300 to 6,500 rpm Max. RCF:4,000 x g Maximum capacity:6 x 15mL conical Timer: 0.5 to 30 minutes or continues with momentary option Dimensions: 8.25 x 9.5 x 7.1 in. Weight: 9lb. (4 Kg) Electrical: 120V ~ 60Hz or 230 V ~ 50Hz Description: Select Spin spectra 6C, complete with 6 x 15 ml rotor Combination adapters for 5 ml (12x 75mm) and 7ml (13 x 100 mm) tube sizes pk.of 6 230V includes both EU and UK Power codes UK/ USA? Japan	2		
8.	Urine Meter Urine Analyzer provide dependable urine strips results to detect early stages of many disease such as diabetes, kidney disease and urinary track infection. Instrument read results have long proven to be advantageous for both, busy health care professionals and patients. URYXXON® Relax readings eliminate the subjectivity of visual color interpretation. The comprehensive interface option and the optimize print out minimize risks associated with manual transcriptions. Reliable results can be obtained virtually immediate at the point of care. The URYXXON® Relax makes urinalysis simpler and more reliable. 7 Convincing features for optimized usability Non-touch operation Graphic Display Touch Screen Interface Option Small Footprint for Mobile Operation Power supply with battery is possible Memory for 200 measurements Technical data: Measurements: 50 Strips / h Dimensions: 20 x 16 x 7.5 cm (D x W x H) Weight: approx. 710 g Power Requirement: 110-240 VAC, automatic Interfaces: RS232 and USB for connection to PC, PS/2 for the connection of barcode reader and/ or keyboard.	4		

	Memory:200 measurements with ID and date Humidity range:20 – 80% rh Calibration:Automatic, self calibrating				
9.	Wire Gauge Abessestors	8			
10.	Alubumino Meter	2			
11.	Beaker 1 litter	6			
12.	Beaker 2 Litter	4			
13.	Bottles reagents glass steperred Narrow mouth 250 ml	12			
14.	Bottles reagents glass steperred Narrow mouth 500 ml	12			
15.	Cylinders graduated neasuring 1 litter	2			
16.	Funnels 7" Diameter	2			
17.	Slides Microscopic	200			
18.	Tube centrifuge Conical 15 ml	24			
19.	Urine Glass	4			
20.	Chamber Naubaur	2			
21.	Chamber Naubaur Cover Clips	50			
22.	ESR Stand for 06 Tubes	2			
23.	ESR Tube	10			
24.	Haemoglobin Meter Shalls Complete	2			
25.	Haemoglobin Meter for tubes	6			
26.	Haemoglobin Meter for Pipette	2			
27.	Stop Watch	2			
28.	Sprit Lamp	2			
29.	Test Tubes	24			
30.	Test Tube Stand	2			
31.	Test Tube Holder	2			
WARD	WARD EQUIPMENTS & OTHERS				
1.	Temperature holder 15" x 9"	10			
2.	Plain Beds Iron. Main Frame made by 1 x 2 x 18 gauge legs made by 1 ½ x 1 ½ x18 gauge M.S pipe with chainers made by 22 gauge sheets and the Bed is powder coating. 78 x 36 x 24	60			
		1			

3.	Main Frame made by 1 ¼ x 2 ½ x 16 gauge upper frame 1 ¼ x1 ¼ x16 legs made by 2 x 2 x16 gauge M.S pipe with 5" imported wheels chainers made by 18 gauge sheets and the Bed is finish by powder coating.	4	
4.	Made by 22 gauge sheet with one Space and a Cabinet with 2 inch wheel Finished by epoxy powder coated Top is made by Fiber material is very strong and water proof Draw panel and Door is made by Fiber material door is hang by Stainless steel Hanger Finished by Scratch and chip resistance powder coating. Locally Made Export Quality	14	
5.	Sputum Cups SS with cover	20	
6.	Urinal male	10	
7.	Urinal Female	10	
8.	Ward Trolley Dirty Linen Trolley Made by 1 inch round pipe in 18 gauge with Parachute Bag Trolley Frame is finished with epoxy powder coating Locally Made Export Quality	4	
9.	Patients Trolley (Stretcher Trolley) Made by 1 ¼ Stainless steel square pipe in 16 gauge with Stretcher made in 1 ¼ Round pipe in Stainless Steel with Curve sheet 6 inch imported Casters Locally Made Export Quality	2	
10.	Suction Machine Manufactured in grey white ABS(RAL 9002) high strength 4 extra strong wheels (1of them antistatic and 2 of them with brakes Gauge: 0-100 KPa/ 0-760mmHg ON/OFF switch Suction Control Knob Cable Length:3m Long life piston type, oil free maintenance not required 2 Polycarbonate collection jar (4 liters-Scale up to 3500 ml) with safety valve	2	

			_
	to prevent overfilling Collection jar support according to: EN 12218: 1998		
	1 with each collection jar Hydrophobic PTFE filter. It guarantees a particle retention efficiency		
	of 999,95% and bacterial challenge efficiency of 99,99%		
	3m Pvc Suction Tube (Ø8 mm inside – Ø13 mm outside)		
	Maximum Pump Flow 40L/min Maximum Vacuum 0-86 kPa -866mbar -		
	650mmHg Noise Level 45 db(A)/1 m Power 250 W		
	Voltage 200-240 Vac (50-60 Hz)		
	UK/USA/EEC		
11.	Syringe Sterilizer	2	
12.	Oxygen Cylinder Bullnose	4	
13.	BP Apparatus mobile dial type	10	
14.	Split Air Conditioner 1.5 Ton With stabilizer and fitting	4	
15.	Refrigerator 10 cft for two doors	2	
16.	Electric Water Cooler stander size	2	
17.	Re-Chargeable emergency Portable Faluroscent Lamp (Tube Light)	2	
18.	Wheel Chair stander size	2	
	Diesel Generator 30 KV		
	Output Prime Rating :30KVA, 24KW, Output Standby Rating : 33KVA, 26, 4KW, 380/415 V, 3 Phase, 4-wire, 50Hz, 0.8 PF @ 1500 RPM. Starting batteries, exhaust silencer, control panel,		
19.	incorporating Automatic Engine Shutdown in the event of high engine coolant temperature & low lube oil pressure, voltmeter, ammeter, frequency meter, hours counter, Load output circuit Breaker panel and standard manufacturer handbook.	2	
	Made: USA / UK / Japan		
BEDDIN	IG /LNEN ITEMS		
1.	Mattresses for Hospital Beds size: 6' x 3' x 4" 10	14	
2.	years warranty Draw Sheet 72" x 60"	50	
3.	Bed Sheets 90" x 40"	50	
4.	Blankets Red	50	
			1

5.	Pillow 24" x 12"	50	
6.	Pillow covers	50	
7.	Hand Towels Medium size	20	
8.	Operation Gown	10	
9.	Operation Towels	10	
10.	Operation sheets	20	

N.B:-

The original catalogue must accompanied will offer and the equipment should employee/certified at CCE/FDA. Standards.

The bidder must confirm fee Installation /Demonstration at consignee end.

Two years fee services from the date of installation 05 years tube warranty / service contract and available of spare parts may also be confirmed by the bidders.

Sole agent certificate Authorized letter from the manufacture must be provided by the bidder The Service manual with circuit diagram will be provided with all above mentioned items.

The supplier will be bound to supply the price list of spare parts and consumable at the time of tender i.e for two years.

The supplier will be bound to provide fee service during warranty period and to supply spare parts accessories of the supplied equipment on demand.

Joint inspection will be carried out by the consignee & representative of industries Directorate Sindh with technical assistance from concerned specialties end user.

Guaranteed presence of manufacture's trained service engineer in Karachi.

Present of manufacture engineer and specialist during commissioning phase.

In case of CIF the bidder to invest his money for L.C and pay L.C Charges. Transport to consignee and, certificate will be issued by the consignee that the import has been made for the hospital / health facility so has to avail the facility of exemption of duties /taxes as per Government Rules.

DELIVERY:	VALIDITY

General Conditions & Instructions:

- 1.1 The tenders shall be submitted with all documents and drawing literature & catalogue (in equipment) in Technical proposal, with sealing wax. The envelope must contained tender enquiry no on the top and **TECHNICAL /FINANCIAL PROPOSAL** clearly in order to avoid any confusion. The name of manufacturer and the supplier should be affixed on the face of envelope at the left side.
- 1.2 Tenders must be filled in with Blue or black ink in the column provided and on separate letterhead duly signed.
- 1.3 The tenders must be free from erasing, cutting and over writing. In case of erasing, cutting and over writing, authorized person should be initial it.
- 1.4 The rates of each item should be written in figures as well as in words. In case of discrepancy the price in words will be taken as authenticate and final.
- 1.5 Conditional tenders will be ignored and will not be considered /entertained /accepted.
- 1.6 Tender from shall be accompanied by Earnest Money @ 2.5% of the value of stores quoted by them in form of call deposit/bank guarantee.
- 1.7 Original purchase receipt must be enclosed with their offer.
- 1.8 The tendered rate should be inclusive of all taxes, income and sales tax etc payable to federal and provincial Govt. or local bodies and no claims on these account shall be entertained.

- 1.9 The bidder shall furnish General Sales Tax (GST) Registration certificate of the firm failing which the offer will be ignored in case the item is exempted from GST either documentary evident or certificate from competent authority shall be attached with the offer.
- 1.10 The bidder shall furnish copy of valid professional tax certificate and Income tax certificate.
- 1.11 The original catalogue must accompany with offer and the equipment should comply/certified at CE/FDA standards.

2. SPECIAL CONDITION:

- 2.1 Store is required immediately. The tenderer may, however give their short guaranteed delivery period by which the supply will be completed positively.
- 2.2 Tenderers are required to specify make, country of origin and furnish detailed technical description literature/catalogue along with their offer.
- 2.3 The bidders shall quote their firm and final price both in figure and words on "Free delivery basis to consignee end.
- 2.4 Choice to select/ignore any their alternate offers shall rest with the purchaser.
- 2.5 No Manufacturer shall authorize their distributor/agent/any firm or person to quote the same item which manufacturer is quote it-self in any tender. Failing that offer of both the manufacturer as well as other bidder shall be ignored.
- 2.6 Tenders shall purchase separate tender documents and furnish purchases receipt for each alternate offer in case they want to submit alternate offer for any item. All the bids with alternate offers without separate purchase receipt (original) are suppose to be rejected.
- 2.7 The bidder shall confirm the refund of cost difference if the same goods is/was supplied at lower rates to any other Govt. Semi Government Institution or Armed Forces in the provide or outside in the same fiscal year.
- 2.8 The Bid shall comprise a single package containing two separate envelops. Each envelops shall contain separately the financial proposal and the technical proposal.
- 2.9 The envelops shall be marked as "FINANCIAL PROPOSAL" and TECHNICAL PROPOSAL" in bold and legible letters to avoid confusion.
- 2.10 Initially only envelops marked as "TECHNICAL PROPOSAL" shall be opened.
- 2.11 The envelop marked as "FINANCIAL PROPOSAL" shall be retained in the custody of the producing agency without being opened.

3. Purchaser's right to vary quantities at time of award.

The purchaser reserves the right to increase/decrease or delete the quantities of goods etc at the time of award of contract and also reserves the right to enhance the quantity by 25% of goods and services originally specified in the schedule of requirements without any change in unit price of other terms and conditions of goods at any time during contract period.

4. Notification of Award/Advance contract:

- 4.1 Prior to the expiration of the period of bid validity, the purchaser will notify the successful bidder in writing, delivery by hand or by register letter by cable to be confirmed in writing by register letter that is bid has been accepted.
- 4.2 The notification of award will constitute the formation of the contract.

5. Award of contract and contract agreement

Subject to the fulfillment of all codal formalities, the purchaser will award the contract to the successful bidder who's bid has been determined to be qualified to perform the contract satisfactory.

6. Performance Security

The successful tenderers will have to deposit with the purchase security deposit as under in shape of call deposit/pay order at the rate of 2.5% of the value of contract.

7. Criteria for evaluation of bids"

- a. Quoted price
- b. Specification compliance/preferred function
- c. After sale service facility (in case of equipment)
- d. Operational cost (in case of equipment and vehicle)
- e. Delivery schedule
- f. Authority letter from Manufacturer
- g. Earnest Money
- 8. Bidder must attached/product the following documents.
- 1. Registration Certificate issued by the industries department
- 2. Income Tax Registration Certificate\
- 3. General Sales Tax Certificate issued by the sales tax department
- 4. Professional sales Certificate
- 5. Chamber of Commerce Certificate
- 6. Business Experience No of Year Certificate
- 7. Annual Turn over in Million Certificates
- 8. Client Certificate stamp paper
- 9. Income Tax Annual returns 02 years
- 10. Audit report of sales Tax last 03 years
- 11. Monthly sale Tax Challan summary of 15 months
- 12. Relevant Experience in same field
- 13. No Objection Certificate.

9. Fee for Award of Contract:

Service charges @ .25% of the value of the contract will realized /charged by the AG Sindh, while making payment to the contractors for award of each contract

10 Undertaking

- O9.1 That I/We agree whether our tender accepted for total, partial or enhanced quantity for all or any single item. I/We also agreed to supply and accept the said item at the rates for the supply of contracted quantity with in the stipulated period shown in the contract.
- 09.2 I/We understand and confirm the refund of cost different if the same goods is/was supplied at lower rates to any other Govt./Semi Govt. institution in the province in the same fiscal year .
- 09.3 I/We undertake that; if any of the information submitted in accordance to this tender enquiry found incorrect our contract may be cancelled at any stage on our cost and risk.

Note: Furniture final approval/ decision would be taken on samples provided by bidders.

CERTIFICATE

We guarantee to supply the sores exactly in accordance with the requirement specified in the invitation to this tender.

Signature of tenderer :	
Name & Designation :	
Address:	

OFFICE OF THE DISTRICT HEALTH OFFICER UMERKOT

PHONE NO 0238571458 FAX No. 0238-570039

NO.EDOH/U.KOT/ (Account:) /- 761/64 Dated: - 18-4-2012

TENDER FOR PURHCASE OF MACHINARY INSTRUMENTS/EQUIPMENT/FURNITURE/FIXTURE /BEDDING LINEN FOR THE YEAR 2011-12

TENDER NOTICE

The District Health Officer Umerkot is hereby invites sealed bids according to SPPRA Rules from various Manufacturers/Importers/distributors for the supply of items mentioned in the tender. A complete set of tender enquiry may be purchased from the office of undersigned, PM & I Cell Health Department , Block -24 Shahrah-e- Liaquat Karachi & Directorate General Health Services Sindh Hyderabad, on submission of written application upon cash payment of non-re-fundable fee mentioned in each tender enquiry. The bids must be delivered on opening date 16-05-2012 at 2.00 PM which will be opened publicly in the presence of the bidders or their authorized representatives who choose to attend at 2.00 PM 16-05-2012.

All bids must be accompanied by a bid security @ 2.5% of the total bid cost in shape of Pay orders/Bank Drafts.

The purchaser reserves the right to accept /reject any/all bids under the relevant provision of SPPRA Rules 2010.

Sr.#	Date of Sale	Date of Deposit	Date of Opening	Tender Fee
1	30-04-2012 During office Hours	16-05-2012 (upto1.00PM)	16-05-2012 at 2.00 PM	Rs. 1000

N.B.

- The tenders will be sold from 30-04-2012 at the office of undersigned, PM & I Cell Health Department , Block -24 Shahrah-e- Liaquat Karachi & Directorate General Health Services Sindh Hyderabad Bids must be in Pak rupees
- 2. In case Government announces any Public Holiday then tender will be opened on next working day,
- 3. All quotations shall include Govt: Taxes including GST if applicable.

Address: DISTRICT HEALTH OFFICER UMERKOT

In the premises of SOORAH BADSHAH COMPLEX UMERKOT

(DR. ABDUL AZIZ KUNBHAR) DISTRICT HEALTH OFFICER UMERKOT

C.C to:-

The Director Public Procurement Regulatory Authority Karachi. He is requested to please post the above tender on the web site of SPPRA

The Additional Secretary (PM&I Cell) Health Department Block-24, Shahrah-e-liaquat Karachi.

The Director General Health Services Sindh Hyderabad.

Phone No. 0238571458 & FAX NO.0238570039

OFFICE OF THE DISTRICT HEALTH OFFICER UMERKOT

NO.EDOH/U.KOT/ (Account)/ 761/64

Dated:- 18-04-2012

To,

The Director Information Advertisement Publication Department 95/96 Pakistan Secretariat Karachi.

Subject:-

to this office.

RELEASE OF GOVERNMENT ADVERTISEMENT IN LEADING NEWSPAPERS.

The Tender Notice (six copies) for purchase of

Instrument / Equipment/furniture & Linen items, are sent herewith for publication in the leading News papers including daily Kawish / (Sindhi) Jang (Urdu) and Dawn (English).

It is requested that the attached Tender may please be printed/ Inserted in at least three daily Newspapers mentioned above at the earliest under intimation

The bill for necessary payment may please be sent in Duplicate, for which budgetary provision are available.

(DR. ABDUL AZIZ KUNBHAR)
DISTRICT HEALTH OFFICER
UMERKOT

C.C. to:-

The Director Public Procurement Regulatory Authority Karachi. He is requested to please post the the same on the web site of SPPPRA.

The Additional Secretary (PM&I Cell) Health Department Block-24, Shahrah-e-liaquat Karachi.

The Director General Health Services Sindh Hyderabad.