

OFFICE OF THE EXECUTIVE ENGINEER BUILDING DIVISION NO:-III AKRACHI

Tender From issued to M/s: **Government Contractor.**

Charge to Rs:-3000/=

Vide D.R.No: Dated the:- 2015

EXECUTIVE ENGINEER
BUILDING DIVISION NO:-III
KARACHI

NAME OF WORK:- **REHANILITATION / IMPROVEMENT OF ROADS CONSTRUCTION OF CC STREETS**
& PROVIDING AND LAYING SEWERAGE SYSTEM IN MUJAHID COLONY
LIAQUATABAD ZONE DISTRICT (CENTRAL) KARACHI

I/We hereby tender for execution of the works of Government of Sindh herein before/after referred to as Government of the work specification in the written memorandum with time specification in each memorandum at:-

I.	Civil/Road Work	% At Par/Above/Below
----	-----------------	----------------------

(CONTRACTOR SIGNATURE)

EXECUTIVE ENGINEER
BUILDING DIVISION NO:-III
KARACHI

The estimate carried out & according to all respect with the specification design/drawing & instruction in writing referred to rule-I here of the clause-12 of the annexed condition of the contract & agreement that when material for the work are provided by the Government such material & rate to paid for then shall be as provided in Schedule 'B' here to:-

GENERAL DESCRIPTION

i.	Estimated Cost	Rs:-17.979-Million
ii.	Earn Money 2%	Rs:-0.359-Million
iii.	S/Deposit in/c: E/Money 10%	Rs:-1.797-Million
iv.	Income Tax will be deducted 7.50%	Rs:-1.348-Million
v.	Time of Completion of work:-	Rs:-12-Months

I/We have offered the above rates after taking into consideration all the terms & conditions as per B-I printed tender & this form so as to completed the agreement, In case of Failure the Department will be at liberty to take action me /us.

i	Schedule-A	Nil
ii	Schedule-B	Attached herewith

Call Deposit/Pay order bearing No:-_____ Dated:-_____
 Amounting to Rs:-_____ Bank_____ Branch Karachi
 Is enclosed herewith as desired on account of Security Deposit

(CONTRACTOR SIGNATURE)

REHABILITATION / IMPROVEMENT OF ROADS, CONSTRUCTION OF CC STREETS & PROVIDING AND LAYING SEWERAGE SYSTEM IN MUJAHID COLONY LIAQUATABAD ZONE, DISTRICT (CENTRAL) KARACHI

SCHEDULE B....

S.NO	ITEM OF WORK	Unit	Quantity	Rate	Amount (Rs)
1	Earth work excavation undressed lead upto a single throw of Kassi Phawarh or Shovel in Ordinary Soil etc complete. (Vol-III, Part-III, Chap-1, Pg-1, Sr. 1-a)	%Cft	66872.00	1361.25	91029.51
2	Dismantling of Cement Concrete Palin 1:2:4. (Vol-III, Part-III, Chap-2, Pg-10, Sr. 19-a)	%Cft	244.00	3327.50	8119.10
3	Cartage of 100 CFT / 5 tons of all material likes one aggregate, spawl, coal, lime, surkhi etc. B.G. Rait fasterings points & crossing Bridges Girders, Pipes, Sheets Raits, M.S. Bars etc, or 1000 Nos brinks, 10'x5'x3' or 1000 manuds of feul wood by trucks or any other means owned by the contractor (Lead upto 15 Miles etc). (Vol-I, Part-I, Chap-1, Pg-1, Sr. 1)	%Cft	67116.00	1065.04	714812.25
4	Preparing Sub-Base by supplying and spreading well graded pit or bed run gravel having a liquit limt not greater than 25 and plasticity index not greater than 6 in proper camber and grade including watering rolling and compacting in layers, thickness of each compacted layer not exceeding 6" compacted upto 98-100% density as per modified AASHO density (Rate i/c. all cost of material T&P and carriage upto 3 chains) (Vol-III, Part-VI, Chap-1, Pg-4, Sr. 11-C)	%Cft	33716.00	3341.71	1126690.94
5	Providing and laying Aggregate base course in proper grade and camber having CBR 80% as per AASHTO standard specification i/c. spreading and compacting by approved mechanical menas (Motor grader, Vibratory Roller and Smooth wheel roller etc) watering to maintain the moisture content the compaction of each layer shall 100 percent to the max dry density (Rate i/c. all cost of materials T&P and carriage upto 3 chains) (Vol-III, Part-VI, Chap-1, Pg-5, Sr. 12 b)	%Cft	42600.00	5542.24	2360994.24
6	Laying mechanically to proper line and grade plant mixed Asphalt Concrete specifed formula according to job mixed formula approved by the Engineer Incharge rolling and finishing to design proper grade line level and comber etc. (Machinery with POLs Cost of Material Carriage). 1½ Thick Asphalt Concrete Wearing Course Plant Mix (Vol-III, Part-VI, Chap-1, Pg-10, Sr. 24-a)	%Sft	85200.00	6873.79	5856469.08
7	Providing & Fixing Precast Edge Block 3750 Psi Industrail Made Size 6 inches thick x 12 inches long x 12 inches high including the cost of Cartage, excavation, form work for haunching, 1450 PSI lean concrete, 2250 PSI concrete for haunching, 1:4 cement sand mortoz. (Vol-III, Part-VI, Chap-1, Pg-15, Sr. 14)	P.Rft	6800.00	297.01	2019668.00

SCHEDULE B....

S.NO	ITEM OF WORK	Unit	Quantity	Rate	Amount (Rs)
8	Providing and Laying 2" thick topping cement concrete (1:24) including surface finishing and dividing into panels: (Vol-III, Part-II, Chap-8, Pg-42, Sr. 16-d)	%Sft	71800.00	3275.50	2351809.00
9	Excavation for pipe line in trenches & pits & all kind of soil of murum i/c. trimming & dressing sides to true alignment and shape & leveling of beds of trenches to correct level & grade cutting jointing holes & disposable of surplus earth within one chain as directed by Engineer Incharge. (Vol-IV, Part-VI, Chap-2, Pg-61, Sr. 5)	%oCft	55600.00	3600.00	200160.00
10	Providing RCC Pipe of ASTM C-76-62 T/C 76-70 class-II wall B and fixing in trench i/c. cutting, fitting and jointing with rubber ring i/c. testing with water to specified pressure.				
	12" Dia Pipe	P.Rft	800.00	412.00	329600.00
	15" Dia Pipe	P.Rft	300.00	515.00	154500.00
	18" Dia Pipe	P.Rft	200.00	618.00	123600.00
	24" Dia Pipe	P.Rft	1500.00	869.00	1303500.00
	(Vol-VI, Part-VI, Chap-2, Pg-17, Sr. 1-b, c, f)				
11	Construction manhole or inspection chamber for the required diameter of circular sewer and 3'-6" (1067 mm) depth with walls of B.B. in cement sand mortar 1:3 cement plastered 1:3 1/2" thick, inside of walls and 1" (25 mm) Thick over benching and channel i/c. fixing C.I. manhole cover with frame of clear opening 1-1/2' x 1-1/2' (457x457mm) of 1.75 Cwt (88.9 Kg) embedded in plain C.C. 1:2:4 and fixing 1" (25mm) dia M.S. steps 6" (150mm) wide projecting 4" (102mm) from the face of walls at 12" (305mm) CC duly painted etc complete as per standard specification and drawing. (Vol-IV, Part-VI, Chap-2, Pg-46, Sr. 1)	Each	56.00	14748.00	825888.00
12	Refilling the excavated stuff in trenches 6" thick layer including watering ramming to full compaction etc. compete. (Vol-IV, Part-VI, Chap-2, Pg-77, Sr. 24)	%oCft	41700.00	2760.00	115092.00
14	Full hire charges of the pumping set per day inclusive of wage of driver and assistant fuel or electric energy plate form required for placing pump etc. at lower depth with suction and delivery pipe for pumping out water found at various depth from trenches i/c the cost of erection and dismantling after completion of the job. Higher charge of pumping set of upto 10 HP (but not less than 5 HP) pumping out water from 10' deep trench. . (Vol-IV, Part-VI, Chap-2, Pg-76, Sr. 23-1)	P.Day	30	1500.00	45000.00

TOTAL AMOUNT OF SCHEDULE ITEMS RS: 17626932.12

EXECUTIVE ENGINEER
BUILDINGS DIVISION NO:III
(W&S) KARACHI