

SCHEDULE "B"					
IMPROVEMENT / REHABILITATION OF ROAD AND SEWERAGE SYSTEM IN BLOCK 5 AND 6 F.B AREA CENTRAL KARACHI					
Engineer's Estimates / Abstract of Cost					
SR. #	Description	Unit	Quantity	Rate	Amount (Rs)
Road Work (SCHEDULE ITEMS)					
1	scarifying the existing road surface	% Sft	112152.00	116.16	130,276
2	Earth work excavation in irrigation channels drain etc, dressed to designed section grade and profile excavated material disposed off and dressed within 50ft lead in ordinary soil	%o Cft	15768.00	2,420.00	38,159
3	Providing R.C.C Pipe of ASTM C-7662 T/C 7670 class ii wall B and fixing in trench I / c cutting fitting and jointing with rubber ring I / c testing with water to specified pressure.				
	FOR SEWERAGE LINE 12 "	P.Rft	900.00	412.00	370,800
4	Constructing manhole or inspection chamber for the required diameter of circular sewer and 3'-6" (1067 mm) depth with walls of B.B in cement sand mortar 1:3 cement plastered 1:3, 1/2" thick, inside of walls and 1" (25 mm) thick over benching and channel i/c fixing C.I manhole cover with frame of clear opening 1-1/2' x1-1/2' (457x457 mm) of 1.75 cwt. (88.9 kg) embaded in plain C.C 1:2:4 and fixing 1" (25 mm) dia M.S steps 6" (150 mm) wide projecting 4" (102 mm) from the face of wall at 12" (305 mm) C/C duly painted etc. Complete as per standard specification and drawing.	Each	33.00	14,748.00	486,684
5	preparation of sub grade i/c Earth Excavation filling to an average Depth of 9" design to camber / side slope and consolidation with power roller	% Sft	112152.00	526.28	590,234
6	Providing and laying granular sub-base course using hub gravel with sand and silt form 0 to 60 mm laid in layers i/c compacting up to 98% of maximum dry density determined by AASHTO (T-180 methods) or as directed by the Engineer In charge etc. complete	% Cft	56076.00	3341.71	1,873,897

**SCHEDULE "B"****IMPROVEMENT / REHABILITATION OF ROAD AND SEWERAGE SYSTEM  
IN BLOCK 5 AND 6 F.B AREA CENTRAL KARACHI**

Engineer's Estimates / Abstract of Cost

SR. #	Description	Unit	Quantity	Rate	Amount (Rs)
7	Providing & fixing Precast Edge Block 3750 PSI Industrial Made Size 6 inches thick x 12 inches long x 12 inches high including the cost of Cartage, excavation, form Work for haunching, 1450 PSI lean concrete, 2250 PSI concrete for haunching, 1:4 cement sand mortor.	p/Rft	9346.00	297.01	2,775,855
8	Providing and Laying Aggregate Base Coarse of 80% of CBR as per (AASHTO standard specification ) i/c compacting to require density by the approved mechanical mean ( vibratory roller road packer and smooth wheel roller etc. ) i/c watering with all lead and lift etc., complete accurate compacted thickness shall be considered for the payments and as directed by the engineer in charge	% Cft	56076.00	5542.24	3,107,867
9	Laying to Proper line and grade plant mixed Asphalt concrete paver finished (Hydraulic / Electronic control) Prepared to specified formula according to job mix formula approved by Engineer in charge including rolling and finishing to Proper line, grade level and camber etc.: (Machinery with POLs cost of material carriage).	% Sft	112152.00	8274.73	9,280,275
<b>Total</b>					<b>18,654,046</b>

Add / Deduct \_\_\_\_\_% on I.No. 6 &amp; 8 :-

Rs.

Add / Deduct \_\_\_\_\_% on I.No. 9 :-

Rs.

Add / Deduct \_\_\_\_\_% on I.No. 3 :-

Rs.

Add / Deduct \_\_\_\_\_% on I.No. 4 :-

Rs.

**TOTAL :-**

Rs.

**CONTRACTOR SIGNATURE****EXECUTIVE ENGINEER  
EDUCATION WORKS DISTRICT  
WEST, KARACHI**